

**FLAME-RETARDANT RESIN COMPOSITION**

Patent Number: JP62101644  
Publication date: 1987-05-12  
Inventor(s): HOSHI KAZUO; others: 01  
Applicant(s): SUMITOMO BAKELITE CO LTD  
Requested Patent: ☐ JP62101644  
Application Number: JP19850240532 19851029  
Priority Number(s):  
IPC Classification: C08L23/02; C08K13/06; C08L23/26  
EC Classification:  
Equivalents:

---

**Abstract**

---

**PURPOSE:**To ensure the prevention of dripping during combustion and to prevent harmful gases to be emitted on fire, by blending a specified olefin resin with a hydrated metal oxide having a coupling agent-treated surface, a red phosphorus flame retarder or an org. phosphine derivative and an inorg. filler in a specified ratio.

**CONSTITUTION:**This flame-retardant resin compsn. is formed by blending 100pts. wt. olefin resin (A), obtd. by mixing 5-95wt% polyolefin resin with 5-95wt% at least one silane-grafted polymer obtd. by grafting a silane onto a polyolefin resin, with 50-200pts.wt. hydrated metal oxide (B) having a surface treated with at least one titanate or silane coupling agent, 2-50pts.wt. red phosphorus flame retarder or org. phosphine derivative or mixture of two or more of them (C) and 1-20pts.wt. at least one inorg. filler (D).

---

Data supplied from the esp@cenet database - I2